


GOUPILLES CYLINDRIQUES RECTIFIÉES
DIN 6325 - ISO 8734 - NFE 27475
GROUND DOWEL PINS DIN6325 – ISO8734 – NFE27475



② Désignation : Goupilles cylindriques DIN6325 D x L
 Description: Dowel pins DIN6325 DxL



Matière = Acier trempé revenu pour dureté 58-62 HRC
 Material: Steel hardening and tempering for hardness 58-62 HRC

D m6	L																																
1	4	5	6	8	10	12	14	16																									
1,5	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30																		
2	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45														
2,5	4	5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50													
3		5	6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50	55	60											
4			6	8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50	55	60	70	80									
5				8	10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50	55	60	70	80	90	100							
6					10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50	55	60	70	80	90	100							
8					10	12	14	16	18	20	22	24	26	28	30	32	36	40	45	50	55	60	70	80	90	100	120						
10						14	16	18	20	22	24	26	28	30	32	36	40	45	50	55	60	70	80	90	100	110	120	140	160				
12							16	18	20	22	24	26	28	30	32	36	40	45	50	55	60	70	80	90	100	110	120	140	160				
14									20		24		28	30	32	36	40	45	50	55	60	70	80	90	100	110	120	130	140	150	160		
16											24		28	30	32	36	40	45	50	55	60	70	80	90	100	110	120	130	140	150	160		
18																	40	45	50	55	60	70	80	90	100	120	140	160					
20																30	32	36	40	45	50	55	60	70	80	90	100	110	120	130	140	150	160
25																				50	55	60	70	80	90	100	120						
30																				50	60	70	80	90	100	120							

Boîtes assortiments goupilles voir p. 25
 Boxed sets of pins, see p. 25

- SUR DEMANDE** • Dimensions et tolérances spéciales
 ON REQUEST Other tolerances and dimensions
- Matières spéciales
 Special materials